



ZODZ.E337055 - Positioning Devices

Positioning Devices

[See General Information for Positioning Devices](#)

HILTI AG
 FELDKIRCHER STRASSE 100
 POSTFACH 333
 9494 SCHAAN, LIECHTENSTEIN

E337055

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam.,		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Min. Install. Temp., °C(°F)	Resistant to UV Light	Plenum Rating	Material Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
		mm(in.)			Min	Max					
		Min	Max		Min	Max					
2061192	2,21	2 (0.08)	24 (0.94)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061193	2,21	2 (0.08)	35 (1.38)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061194	2,21	2 (0.08)	55 (2.17)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061195	2,21	2.5 (0.10)	36 (1.42)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061196	2,21	2.5 (0.10)	55 (2.17)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061197	2,21	2.5 (0.10)	80 (3.15)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061198	2,21	3 (0.12)	51 (2.01)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061199	2,21	5 (0.20)	76 (2.99)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061240	2,21	5 (0.20)	101 (3.98)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061241	2,21	5 (0.20)	123 (4.84)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061242	2,21	5 (0.20)	44 (1.73)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061243	2,21	5 (0.20)	76 (2.99)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only

2061244	2,21	5 (0.20)	101 (3.98)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061245	2,21	20 (0.79)	160 (6.30)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
2061246	2,21	32 (1.26)	222 (8.74)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340157	2,21	2 (0.08)	24 (0.94)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340158	2,21	2 (0.08)	35 (1.38)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340159	2,21	2 (0.08)	55 (2.17)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340160	2,21	2.5 (0.10)	36 (1.42)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340161	2,21	2.5 (0.10)	55 (2.17)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340162	2,21	2.5 (0.10)	80 (3.15)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340164	2,21	2 (0.08)	24 (0.94)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340165	2,21	2 (0.08)	35 (1.38)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340166	2,21	2 (0.08)	55 (2.17)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340167	2,21	2.5 (0.10)	36 (1.42)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340168	2,21	2.5 (0.10)	55 (2.17)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340169	2,21	2.5 (0.10)	80 (3.15)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340170	2,21	3 (0.12)	51 (2.01)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340171	2,21	5 (0.20)	76 (2.99)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340172	2,21	5 (0.20)	101 (3.98)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340173	2,21	5 (0.20)	44 (1.73)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340174	2,21	5 (0.20)	76 (2.99)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340175	2,21	5 (0.20)	101 (3.98)	460 (103)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only

340176	2,21	10 (0.39)	140 (5.51)	980 (220)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340177	2,21	2 (0.08)	24 (0.94)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340178	2,21	2 (0.08)	35 (1.38)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340179	2,21	2 (0.08)	55 (2.17)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340180	2,21	2.5 (0.10)	36 (1.42)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340181	2,21	2.5 (0.10)	55 (2.17)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340182	2,21	2.5 (0.10)	80 (3.15)	150 (34)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only
340183	2,21	3 (0.12)	51 (2.01)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	-	V-2	Type 2 Only

[^] - Eligible to be marked "IEC 62275" and "EN 62275" on Type 2 products only.

Last Updated on 2020-01-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"