



Other Fire Protection Products | Explosive Driven Fasteners | **Fasteners, Explosive-Driven**

Explosive-Driven Fasteners

Product Description

Model No	Rod Size Inch	For Use In	Max Pipe Size	
			in	(mm)
W10-30-27P10	3/8	Concrete	2	(50)
W10-30-27P10	3/8	"	3 1/2	(90)
W10-30-27P10	3/8	"	5	(125)
W10-30-32P10	3/8	"	2	(50)
W10-30-32P10	3/8	"	3 1/2	(90)
W10-30-32P10	3/8	"	5	(125)
W10-30-42P10	3/8	"	2	(50)
W10-30-42P10	3/8	"	3 1/2	(90)
W10-30-42P10	3/8	"	5	(125)
W10-30-47P10	3/8	"	2	(50)
W10-30-47P10	3/8	"	3 1/2	(90)
W10-30-47P10	3/8	"	5	(125)
EW10-30-15P10	3/8	Steel	2	(50)
EW10-30-15P10	3/8	"	3 1/2	(90)
EW10-30-15P10	3/8	"	5	(125)
X-EW6H-11-9 FP8	1/4	Steel	3 1/2	(90)
X-EW6H-11-9 P12	1/4	Steel	3 1/2	(90)
X-EW6H-20-9 FP8	1/4	Steel	3 1/2	(90)
X-EW6H-20-9 P12	1/4	Steel	3 1/2	(90)
X-EW6H-28-9 FP8	1/4	Steel	3 1/2	(90)
X-EW6H-28-9 P12	1/4	Steel	3 1/2	(90)
X-EW6H-38-9 FP8	1/4	Steel	3 1/2	(90)
X-EW6H-38-9 P12	1/4	Steel	3 1/2	(90)
X-HS W6 U19 P8 S15	1/4	Steel	3 1/2	(90)
X-HS W10 U19 P8 S15	3/8	Steel	5	(125)
X-EW10H-30-14 P10	3/8	Steel	5	(125)



These fasteners are also FM Approved for horizontal installation. Max pipe size 3 ½ in. (89 mm).

Details

Category	Fasteners, Explosive-Driven
Class of Work	1956 - Explosive-Driven Fstnr, Pipe
Approval Standard	FM 1956 - Explosive-Driven Fasteners
Certification Type	FM Approved
Listing Country	United States of America

Company

Hilti Inc.

7250 Dallas Pkwy, Legacy Tower,
Suite 1000, Plano , Texas 75024

United States of America

<http://hilti.com>