



Easily fastened. In seconds!

Hilti. Outperform. Outlast.

Hitti = registered trademark of Hitti Corp., Schaan | W 3429 0707 0-en | 1 Printed in Liechtenstein | © 2007 | Right of technical and programme changes

Applications

Fastening grating on steel structures in refineries, chemical plants, civil and industrial facilities

Advantages

- Easy to install by a single user, from the top of the grating. Fits easily into 30 x 30 mm mesh grating plates
- Convenient and simple to use
- Fastened with a standard screwdriver
 No additional tool required
- One item to cover various grating heights
- Removable and reusable
- Ready-to-use fastener. No preassembly needed
- Fast installation: up to 180 fasteners per hour
- Hot-dip galvanized for outdoor use and/or moderately corrosive environment (not for off-shore use!)

Highlight

Extremely simple and easy-to-use grating fastening system. The perfect solution for small grating projects.

Ingeniously simple. Fastening gratings has never been easier.

Simplicity doesn't rule out high performance! The Hilti X-MGR grating fastener brings innovation to traditional clamping methods. Get the job done more easily than ever before!







The X-MGR is designed to bring maximum flexibility, wherever the cross bars are positioned.

Performance data

Coating specification:	Hot-dip galvanized, 60 μm
Recommended load (Nrec):	0.6 kN
Grating plate height:	25 mm to 40 mm
Base material thickness:	3 – 25 mm
Tightening torque:	5 – 8 Nm

Right of technical changes reserved.

Fasteners

Ordering designation	Bit dimension	Quantity	Item no.
X-MGR M60	HEX6	20	384233
X-MGR W60	HEX ¼"	20	384234

Accessories

Ordering designation	Bit dimension	Quantity	Item no.
S-B HEX6 bit	HEX6	10	385928
S-B HEX 1/4" bit	HEX ¼"	10	385929

Productivity plus







Powerful combihammers for tough drilling jobs



Anchors and steel screws for all common fastening applications and materials



High-performance cordless screwdrivers with perfectly-matched accessories

Hilti. Outperform. Outlast.