# **SAFETY DATA SHEET**



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Tribol GR 400-3 PD
Product code 468715-DE03
SDS # 468715
Product type Grease

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

General use of lubricants and greases in vehicles or machinery-Industrial General use of lubricants and greases in vehicles or machinery-Professional

Use of the substance/ Grease for industrial applications.

mixture For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

1.3 Details of the supplier of the safety data sheet

Supplier Nordic Lubricants AB

Hemvärnsgatan 9, Solna, 17154, Sweden

+46 (0)770456711

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

**EMERGENCY** Carechem: +44 (0) 1235 239 670 (24/7)

**TELEPHONE NUMBER** 

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word No signal word.

Hazard statements H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** P273 - Avoid release to the environment.

Response Not applicable.

Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazardous ingredients Not applicable.

**Supplemental label** Contains Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:

elements 5-1:3), Reaction products of triphenyl phosphite and isodecanol (1:1) and 2,6-di-tert-butyl-

4-nonylphenol. May produce an allergic reaction.

EU Regulation (EC) No. 1907/2006 (REACH)

Product nameTribol GR 400-3 PDProduct code468715-DE03Page: 1/16Version 10Date of issue 9 December 2022FormatSwedenLanguageENGLISH

Date of previous issue 12 May 2021. (Sweden)

## **SECTION 2: Hazards identification**

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

**Special packaging requirements** 

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger

Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006,

Annex XIII.

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

Defatting to the skin.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a

major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

# SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Product definition Mixture

Highly refined mineral oil and additives. Thickening agent.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Sistillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥25 - ≤50	Not classified.	-	[2]
Distillates (petroleum), solvent- dewaxed heavy paraffinic		≥25 - ≤50	Not classified.	-	[2]
Lithium 12-hydroxystearate	EC: 231-536-5 CAS: 7620-77-1	≤10	Not classified.	-	[2]
castor oil, hydrogenated, lithium salt	EC: 265-222-4 CAS: 64754-95-6	≤3	Not classified.	-	[2]
Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)	REACH #: 01-0000016000-92 EC: 412-780-3 Index: 042-004-00-5	<1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Reaction products of triphenyl phosphite and isodecanol (1:1)	REACH #: 01-2119968254-31 EC: 701-341-4 CAS: -	<1	Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Chronic 2, H411	-	[1]
Sulfuric acid, zinc salt (1:1), monohydrate	EC: 231-793-3 CAS: 7446-19-7 Index: 030-006-00-9	<1	Acute Tox. 4, H302 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/ kg M [Acute] = 1 M [Chronic] = 1	[1]
2,6-di-tert-butyl-4-nonylphenol	REACH #: 01-2120759723-46 EC: 224-320-7 CAS: 4306-88-1	≤0.3	Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]

## See Section 16 for the full text of the H statements declared above.

**Type** 

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Product nameTribol GR 400-3 PDProduct code468715-DE03Page: 2/16Version 10Date of issue 9 December 2022FormatSwedenLanguageENGLISHDate of previous issue12 May 2021.(Sweden)

# **SECTION 3: Composition/information on ingredients**

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eye contact** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. Check for and remove any

contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before

reuse. Get medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If unconscious, place in recovery position and get medical

attention immediately. Get medical attention if symptoms occur.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

## Potential acute health effects

InhalationNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

**Eye contact** No known significant effects or critical hazards.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Inhalation** Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances

along tissue planes.

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

Use foam or all-purpose dry chemical to extinguish.

Unsuitable extinguishing

media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the

burning product.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

No specific fire or explosion hazard.

**Hazardous combustion** 

Combustion products may include the following:

products

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

metal oxide/oxides

## 5.3 Advice for firefighters

**Special precautions for** 

fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Product nameTribol GR 400-3 PDProduct code468715-DE03Page: 3/16

Version 10 Date of issue 9 December 2022 Format Sweden Language ENGLISH

Date of previous issue 12 May 2021. (Sweden)

# **SECTION 5: Firefighting measures**

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Provide adequate ventilation. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

Small spill Move containers from spill area. Vacuum or sweep up material and place in a designated,

labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a

designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent.

Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 7.1 Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid contact of spilt material and runoff with soil and surface waterways. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations See section 1.2 and Exposure scenarios in annex, if applicable.

Product name Tribol GR 400-3 PD Product code 468715-DE03 Page: 4/16 Date of issue 9 December 2022 Language ENGLISH Version 10 Format Sweden (Sweden)

12 May 2021. Date of previous issue

# SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

## Occupational exposure limits

#### Product/ingredient name

#### **Exposure limit values**

Signification of the first of t mineral oil] Absorbed through skin.

> Work environment authority Regulation 2018:1 (Sweden). [oil mist, incl. oil fumes]

TWA: 1 mg/m<sup>3</sup> 8 hours. Issued/Revised: 8/2018 Form: mist and fume STEL: 3 mg/m3 15 minutes. Issued/Revised: 8/2018 Form: mist and fume

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Work environment authority Regulation 2018:1 (Sweden). [old used mineral oil] Absorbed through skin.

Work environment authority Regulation 2018:1 (Sweden). [oil mist, incl. oil fumes]

TWA: 1 mg/m³ 8 hours. Issued/Revised: 8/2018 Form: mist and fume STEL: 3 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 8/2018 Form: mist and fume

Lithium 12-hydroxystearate

Work environment authority Regulation 2018:1 (Sweden). [lithium and comp.]

STEL: 0.02 mg/m³ 15 minutes. Issued/Revised: 8/2018 Form: inhalable fraction

castor oil, hydrogenated, lithium salt

Work environment authority Regulation 2018:1 (Sweden). [lithium and comp.]

STEL: 0.02 mg/m³ 15 minutes. Issued/Revised: 8/2018 Form: inhalable fraction

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

**Recommended monitoring** procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## **Biological exposure indices**

Product/ingredient name

**Exposure indices** 

No exposure indices known.

**Derived No Effect Level** 

No DNELs/DMELs available.

## **Predicted No Effect Concentration**

No PNECs available

## 8.2 Exposure controls

**Appropriate engineering** controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

## **Individual protection measures**

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Product name Tribol GR 400-3 PD Product code 468715-DE03 Page: 5/16 Date of issue 9 December 2022 Format Sweden Language ENGLISH Version 10 (Sweden)

12 May 2021. Date of previous issue

## **SECTION 8: Exposure controls/personal protection**

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# Eye/face protection Skin protection Hand protection

Safety glasses with side shields.

#### **General Information:**

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

#### Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

## Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

#### **Glove Thickness:**

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
  - Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well

Product nameTribol GR 400-3 PDProduct code468715-DE03Page: 6/16Version 10Date of issue 9 December 2022FormatSwedenLanguageENGLISHDate of previous issue12 May 2021.(Sweden)

# **SECTION 8: Exposure controls/personal protection**

as a chemical) risk i.e. where there is abrasion or puncture potential.

**Skin and body**Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots

will be required.

Refer to standards: Respiratory protection: EN 529

Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149

Filtering half-mask with valve: EN 405

Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to

reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state Grease
Colour Brown. [Dark]
Odour Not available.
Odour threshold Not available.
PH Not applicable.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point Open cup: 268°C (514.4°F) [Estimated. Based on Lubricants - Base Oils]

Evaporation rate

Flammability (solid, gas)

Lower and upper explosion

Not available.

Not available.

limit

Vapour pressure Not available.

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method

Relative vapour density

Relative density

Not applicable.

Not available.

**Density** <1000 kg/m³ (<1 g/cm³) at 20°C

Solubility(ies)

Media	Result
<b>w</b> ater	Not soluble

Partition coefficient: n-octanol/

water

Mot applicable.

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available.

Not available.

Product nameTribol GR 400-3 PDProduct code468715-DE03Page: 7/16Version 10Date of issue 9 December 2022FormatSwedenLanguageENGLISHDate of previous issue12 May 2021.(Sweden)

# **SECTION 9: Physical and chemical properties**

Explosive properties Not available.

Oxidising properties Not available.

Particle characteristics

Median particle size Not available.

**9.2 Other information**No additional information.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible

materials for additional information.

**10.2 Chemical stability** The product is stable.

10.3 Possibility of hazardous reactions
 Under normal conditions of storage and use, hazardous reactions will not occur.
 Under normal conditions of storage and use, hazardous polymerisation will not occur.

10.4 Conditions to avoid No specific data.

**10.5 Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.

10.6 Hazardous Under normal conditions of storage and use, hazardous decomposition products should not be

decomposition products produced

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Sodecyl diphenyl phosphite Sulfuric acid. zinc salt (1:1), monohydrate	2500	N/A	N/A	N/A	N/A
	500	N/A	N/A	N/A	N/A

Information on likely Routes of entry

routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

## Potential acute health effects

InhalationNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

InhalationNo specific data.IngestionNo specific data.

**Skin contact** Adverse symptoms may include the following:

irritation dryness cracking

Eye contact No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

## Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Product name Tribol GR 400-3 PD Product code 468715-DE03 Page: 8/16

Version 10 Date of issue 9 December 2022 Format Sweden Language ENGLISH

Date of previous issue 12 May 2021. (Sweden)

# **SECTION 11: Toxicological information**

#### 11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Remarks - Endocrine disruptor - Health 11.2.2 Other information

Not available.

Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Environmental hazards** 

Harmful to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

Not expected to be rapidly degradable.

### 12.3 Bioaccumulative potential

Not available.

## 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

Not available.

Mobility Non-volatile. Grease insoluble in water.

#### 12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting

properties

Not available.

Remarks - Endocrine disruptor - Environment

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 13.1 Waste treatment methods

#### **Product**

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes

<u>European waste catalogue (EWC)</u>

Waste code	Waste designation	
12 01 12*	spent waxes and fats	

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

#### **Packaging**

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations.

Waste code	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

#### **Special precautions**

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Product nameTribol GR 400-3 PDProduct code468715-DE03Page: 9/16Version 10Date of issue 9 December 2022FormatSwedenLanguageENGLISHDate of previous issue12 May 2021.(Sweden)

# **SECTION 13: Disposal considerations**

Methods of disposal

The regulations regarding manufacturers' responsibility for packaging material waste is regulated in "Förordningen om producentansvar för förpackningar". Packaging materials are to be reused or recycled in accordance with the goals outlined in this regulation. The company complies with this manufacturer's responsibility through its association with REPA, which is a subsidiary company of four materials handling companies. The materials handling companies collect, remove and process used and sorted packaging materials through the employment of contractors. Questions regarding collection of packaging materials on a local basis may be directed to the materials company and its contractors. For further information, contact REPA, www.repa.se.

Scrape the package well, recover and add the remainders in the process where the product is used, or send for special waste treatment. Send to a certified recycler/receiver.

References

Commission 2014/955/EU Directive 2008/98/EC

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for

Not available.

14.7 Maritime transport in bulk according to IMO instruments

Not available.

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

EU Regulation (EC) No. 1907/2006 (REACH)

**Annex XVII - Restrictions** 

Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other regulations** 

**REACH Status** 

The company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

**United States inventory** 

Date of previous issue

(TSCA 8b)

All components are active or exempted.

Product name Tribol GR 400-3 PD Product code 468715-DE03 Page: 10/16 Format Sweden Language ENGLISH Version 10 Date of issue 9 December 2022 (Sweden) 12 May 2021.

# SECTION 15: Regulatory information

**Australia inventory (AIIC)** 

All components are listed or exempted.

Canada inventory

At least one component is not listed in DSL but all such components are listed in NDSL.

China inventory (IECSC) All components are listed or exempted. Japan inventory (CSCL) At least one component is not listed Korea inventory (KECI) At least one component is not listed. **Philippines inventory** At least one component is not listed.

(PICCS)

**Taiwan Chemical Substances Inventory** 

(TCSI)

All components are listed or exempted.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

**EU - Water framework directive - Priority substances** 

None of the components are listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

# **SECTION 16: Other information**

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

Road

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

[Regulation (EC) No. 1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SADT = Self-Accelerating Decomposition Temperature

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound

Product name Tribol GR 400-3 PD Product code 468715-DE03 Page: 11/16 Date of issue 9 December 2022 Language ENGLISH Version 10 Format Sweden

(Sweden) 12 May 2021. Date of previous issue

## **SECTION 16: Other information**

vPvB = Very Persistent and Very Bioaccumulative

Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN

01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN

01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN

01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN

01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 /

RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN

01-2119474889-13

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification		Justification
quatic Chronic 3, H412		Calculation method
Full text of abbreviated H	<b>⊮</b> 302	Harmful if swallowed.
statements	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H373	May cause damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Eye Dam. 1 Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1 SKIN SENS. 1B STOT RE 2	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
<u>History</u>		
Date of issue/ Date of revision	09/12/2022.	
Date of previous issue	12/05/2021.	
Prepared by	***	

**▼** Indicates information that has changed from previously issued version.

## Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameTribol GR 400-3 PDProduct code468715-DE03Page: 12/16Version 10Date of issue 9 December 2022FormatSwedenLanguageENGLISHDate of previous issue12 May 2021.(Sweden)



# Annex to the extended Safety Data Sheet (eSDS)

Industrial

## Identification of the substance or mixture

Product definition Mixture

Code 468715-DE03

Product name Tribol GR 400-3 PD

Section 1: Title

Short title of the exposure

scenario
List of use descriptors

General use of lubricants and greases in vehicles or machinery - Industrial

Identified use name: General use of lubricants and greases in vehicles or

machinery-Industrial

Process Category: PROC01, PROC08b, PROC09, PROC02

Sector of end use: SU03

Subsequent service life relevant for that use: No. Environmental Release Category: ERC04, ERC07

Specific Environmental Release Category: ATIEL-ATC SPERC 4.Biv1

Processes and activities covered by the exposure

scenario

Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

## Section 2 Operational conditions and risk management measures

#### **Section 2.1 Control of worker exposure**

No exposure scenario is presented because the product is not classified for Human Health

Contributing scenarios: Operational conditions and risk management measures

## Section 2.2: Control of environmental exposure

Amounts used:

EU tonnage of risk determining substance 2.63

2.63E+3 Tonnes/year

per year:

Frequency and duration of use:

Emission days 300

**Environment factors not influenced by risk** 

management:

Local freshwater dilution factor 10
Local marine water dilution factor 100

Other conditions affecting environmental

exposure:

Negligible wastewater emissions as process operates without water

contact.

Release fraction to air (after typical onsite

RMMs)

5.00E-05

Release fraction to soil from process (after

typical onsite RMMs)

**r** 0

Release fraction to wastewater from process Not available.

(after typical onsite RMMs and before

sewage treatment plan)

**Technical conditions and measures at**process level (source) to prevent release:
Common practices vary across sites thus conservative process release estimates used.

Tribol GR 400-3 PD

General use of lubricants and greases in vehicles or machinery - Industrial

13/16

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Organisational measures to prevent/limit release from site:

Conditions and measures related to sewage treatment plant:

Estimated substance removal from wastewater via on-site sewage treatment

Assumed domestic sewage treatment plant flow rate (m3/d)

Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal as product:

Conditions and measures related to external treatment of waste for disposal:

Conditions and measures related to external recovery of waste:

Prevent discharge of undissolved substance to or recover from onsite wastewater.

User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant

Do not apply industrial sludge to natural soils.

Sewage sludge should be incinerated, contained or reclaimed.

Not available.

2.00E+3

Not available.

External treatment and disposal of waste should comply with applicable local and/or national regulations.

External recovery and recycling of waste should comply with applicable local and/or national regulations.

## Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment): Used ECETOC TRA model (May 2010 release).

**Exposure estimation and reference to its source - Workers** 

**Exposure assessment (human):** No exposure scenario is presented because the product is not

classified for Human Health

# Section 4: Guidance to check compliance with the exposure scenario

Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES
Health	No exposure scenario is presented because the product is not classified for Human Health

Tribol GR 400-3 PD



# Annex to the extended Safety Data Sheet (eSDS)

**Professional** 

#### Identification of the substance or mixture

Product definition Mixture

Code 468715-DE03

Product name Tribol GR 400-3 PD

Section 1: Title

Short title of the exposure

List of use descriptors

scenario

General use of lubricants and greases in vehicles or machinery - Professional

Identified use name: General use of lubricants and greases in vehicles or

machinery-Professional

Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20

Sector of end use: SU22

Subsequent service life relevant for that use: No. Environmental Release Category: ERC09a, ERC09b

Specific Environmental Release Category: ATIEL-ATC SPERC 9.Bp.v1

Processes and activities covered by the exposure scenario

Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

## Section 2 Operational conditions and risk management measures

#### Section 2.1 Control of worker exposure

No exposure scenario is presented because the product is not classified for Human Health

Contributing scenarios: Operational conditions and risk management measures

## Section 2.2: Control of environmental exposure

Amounts used:

EU tonnage of risk determining substance 5.39 Tonnes/year

per year:

Frequency and duration of use:

Emission days 365

Environment factors not influenced by risk

management:

Local freshwater dilution factor 10

Local marine water dilution factor 100

Other conditions affecting environmental

exposure:

Negligible wastewater emissions as process operates without water

contact.

Release fraction to air (after typical onsite

RMMs)

1.00E-04

Release fraction to soil from process (after

typical onsite RMMs)

1E-03

Release fraction to wastewater from process Not available.

(after typical onsite RMMs and before

sewage treatment plan)

Technical conditions and measures at Common practices vary across sites thus conservative process

process level (source) to prevent release: release estimates used.

Tribol GR 400-3 PD General use of lubricants and greases in vehicles or machinery - Professional

15/16

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Organisational measures to prevent/limit release from site:

Conditions and measures related to sewage treatment plant:

Estimated substance removal from wastewater via on-site sewage treatment

Assumed domestic sewage treatment plant flow rate (m3/d)

Maximum allowable site tonnage (Msafe) based on release following total wastewater treatment removal as product:

Conditions and measures related to external treatment of waste for disposal:

Conditions and measures related to external recovery of waste:

Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant

Do not apply industrial sludge to natural soils.

Sewage sludge should be incinerated, contained or reclaimed.

No data available yet

2.00E+3

No data available yet

External treatment and disposal of waste should comply with applicable local and/or national regulations.

External recovery and recycling of waste should comply with applicable local and/or national regulations.

## Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment): Used ECETOC TRA model (May 2010 release).

**Exposure estimation and reference to its source - Workers** 

Exposure assessment (human): No exposure scenario is presented because the product is not

classified for Human Health

## Section 4: Guidance to check compliance with the exposure scenario

Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES
Health	No exposure scenario is presented because the product is not classified for Human Health

Tribol GR 400-3 PD